

303 Booking Cancellation (Ocean)

Functional Group ID=**RO**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Cancellation (Ocean) Transaction Set (303) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide all the information necessary for a shipper or forwarder to cancel a previous booking request.

Page <u>No.</u>	Pos. <u>No.</u>	Seg. <u>ID</u>	<u>Name</u>	Req. <u>Des.</u>	<u>Max.Use</u>	Loop <u>Repeat</u>	<u>Notes and Comments</u>
2	010	ST	Transaction Set Header	M	1		
3	020	B1	Beginning Segment for Booking or Pick -up/Delivery	M	1		
Not Used	030	Y6	Authentication	O	2		
4	040	Y5	Space Booking Cancellation	M	1		
Not Used	050	V9	Event Detail	O	10		
5	060	SE	Transaction Set Trailer	M	1		

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:

Data Element Summary

	Ref.	Data		
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	ST01	143	Transaction Set Identifier Code	M ID 3/3
			Code uniquely identifying a Transaction Set	
			303 X12.110 Booking Cancellation (Ocean)	
M	ST02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	

Segment: **B1** Beginning Segment for Booking or Pick-up/Delivery

Position: 020

Loop:

Level:

Usage: Mandatory

Max Use: 1

Purpose: To transmit identifying numbers, dates, and other basic data relating to the transaction set

Syntax Notes:

Semantic Notes:

- 1 B101 is the Standard Carrier Alpha Code (SCAC) of the carrier sending the EDI transmission.
- 2 B103 is the booking date accepted by the carrier.

Comments:

Data Element Summary

	Ref.	Data	Attributes
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
Must Use	B101	140 Standard Carrier Alpha Code Standard Carrier Alpha Code	O ID 2/4
M	B102	145 Shipment Identification Number Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters)	M AN 1/30
Not Used	B103	373 Date Date (YYMMDD)	O DT 6/6
Must Use	B104	558 Reservation Action Code Code identifying action on reservation or offering R Delete	O ID 1/1

Segment: **Y5** Space Booking Cancellation
Position: 040
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To specify booking number for cancellation
Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary				
	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
M	Y501	13	Booking Number	M AN 1/17
			Number assigned by the carrier for space reservation	

Segment: **SE** Transaction Set Trailer
Position: 060
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:**Semantic Notes:**

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	Ref.	Data		
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SE01	96	Number of Included Segments	M N0 1/10
			Total number of segments included in a transaction set including ST and SE segments	
M	SE02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
			<i>Cite the same value that appears in ST02.</i>	